



STEEL SERVICE CENTRE




Product card

Wall sandwich panel with concealed fastening







Technical information



Panel cross-section




Joining the panels



Technical information

Core	PIR										
Density [kg/m³]	40 ± 3										
PIR panel thickness [mm]	60	80	100	120							
Weight [kg/m ²]	9,5	10,3	11,1	11,9							
Effective width [mm]	1050		·	·							
Total width [mm]	1102										
Min. panel length [m]	2,0										
Max. panel length [m]	15,0										
Outer/inner sheet thickness [mm]	0,3-0,7 / 0,3-0,7										
U-value [W/m²K]	0,37	0,28	0,22	0,18							
Fire spread degree	NRO			·							
Type of external / internal profiling	[M], [T1], [R],	, [F] / [T1], [M], [F]									
External / internal corrosion resistance	C1, C2, C3 (C	4 ÷ C5) / A1 (A2 ÷ A	.5)								
Standard coatings	Poliester Inte MULTILAYER	erior [INT], Polieste 40 [MLT]	r Standard [RAL], H	ERCULIT [HC],							
Special coatings	PVDF, PUR, P	VC (P), PVC (F) - Foo	odSafe								
Accessories	fixing system	n, seals, flashings, r	ooflight								



NOTE! The arrows marked with the symbol **^INT^** on the panel lock point to the **inner side** of the sandwich panel with the **[INT] INTERIOR** coating.

External profiling Internal profiling MICRO RIB [M] 23,65 mm TRAPEZOIDAL[T1] 44,8 mm --**0**,4 mm 1,0 mm TRAPEZOIDAL [T1] 44,8 mm MICRO RIB [M] 23,65 mm 1,0 mm **0**,4 mm RIB [R] 47,29 mm FLAT [F] 1,5 mm ATTENTION! Due to the structure of sandwich panels with FLAT [F] profiles, the so-called effect may occur. "waves" of the sheet metal. This is a natural phenomenon for this type of products. We recommend contacting the technical department to choose the optimal solution. FLAT [F]

Internal and external profiling are available in any configuration.

Coatings and colors

POLIESTER Interior [INT] - Available colors for interior cladding



POLIESTER Standard [RAL] - Available colors for exterior cladding



HC 3009

HC 8004

HC 8017

MULTILAYER 40 [MLT] - Available colors for exterior cladding



HC 7016



Printing technology does not allow faithful rendering of colors. Therefore the colors shown are indicative and may differ from actual colors.



HC 9005

In addition, on individual order, non-standard colors and coatings are available, outside the palette shown (PVDF, PUR, PVC (P), PVC (F) - FoodSafe).

Coating parameters

Code	Coating thickness	Corrosion resistance	UV resistance
POLIESTER Interior [INT]	15 μm	RA2	Not applicable
POLIESTER Standard [RAL]	25 μm	RC3	RUV2
IERCULIT [HC]	35 µm	RC4	RUV4
NULTILAYER 40 [MLT]	40 µm	RC3	RUV3

Notes

		_							_		_					_		
		 											 _					
		_											 					
		 _											 					
						_					_						_	
		_																
		_																
		 	_															

04/2025/EN





Modular roofing tiles
MODULAR SERIES



Retro roof tiles RETRO SERIES



Steel roof gutter system
INGURI



FLAT METAL SHEETS



Roof Sandwich PANELS

Uncoiling and slitting SERVICES

Compact roofing tiles COMPACT SERIES



ROOT PANEL SERIES



TRAPEZOIDAL SHEETS



FLASHINGS



Wall Sandwich PANELS



Flat sheets and cutting SERVICES



Steel roofing tiles CLASSIC SERIES



INTEGRATED **PV PANELS**



STRUCTURAL PROFILES



ACCESORIES



SKRIN, LINEA



PERFORATION of sheets



VSS VSS

